



INVESTOR IN PEOPLE

PCT/IB04/51927

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 30 July 2004


**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

**BEST AVAILABLE COPY**

The  
**Patent  
Office**

06OCT03 E842266-2 D02979  
P01/7700 0 00-0323281/5



**Request for grant of a patent**

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

**The Patent Office**

Cardiff Road  
Newport  
Gwent NP10 8QQ

1.	Your reference	PHGB030175GBP		
2.	Patent application number (The Patent Office will fill in this part)	0323281.6		
		4 OCT 2003		
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	KONINKLIJKE PHILIPS ELECTRONICS N.V. GROENEWOUDSEWEG 1 5621 BA EINDHOVEN THE NETHERLANDS 07419294001		
		Patents ADP Number (if you know it)		
		If the applicant is a corporate body, give the country/state of its incorporation		
		THE NETHERLANDS		
4.	Title of the invention	IMPROVING GREY SCALE CONTRAST IN A 3D IMAGE DISPLAY DEVICE		
5.	Name of your agent (if you have one)			
		"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)		
		Philips Intellectual Property & Standards Cross Oak Lane Redhill Surrey RH1 5HA		
		Patents ADP number (if you know it)		
		08359655001		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority Application number	Date of filing
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:			
		YES		
		a) any applicant named in part 3 is not an inventor, or		
		b) there is an inventor who is not named as an applicant, or		
		c) any named applicant is a corporate body.		
		See note (d)).		

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

## Continuation sheets of this form

Description	11
Claims(s)	5
Abstract	1
Drawings	6

only for

10. If you are also filing any of the following, state how many against each item:

## Priority Documents

Translations of priority documents

Statement of inventorship and right

to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and  
search (*Patents Form 9/77*)

Request for substantive examination  
(*Patents Form 10/77*)

Any other documents

(*Please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date 3/10/2003

12. Name and daytime telephone number of  
person to contact in the United Kingdom

01293 815143

D. T. MURLEY

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## DESCRIPTION

**IMPROVING GREY SCALE CONTRAST IN A 3D IMAGE DISPLAY DEVICE**

The present invention relates to display devices, and in particular to display devices adapted to display three dimensional or stereoscopic images.

5

The generation of three-dimensional images generally requires that a display device is capable of providing a different view to the left and the right eye of a user of the display device. This can be achieved by providing a separate image directly to each eye of the user by use of specially constructed goggles. In one example, a display provides alternating left and right views in a time sequential manner, which views are admitted to a corresponding eye of the viewer by synchronised viewing goggles. In contradistinction, the present invention relates to classes of display devices where different views of an image can be seen according to the viewing angle relative to a single display panel. Hereinafter, these will be referred to generally as 3D display devices.

15

One known class of such 3D display devices is the liquid crystal display in which the parallax barrier approach is implemented. Such a system is illustrated in figure 1.

With reference to figure 1, a display device 100 of the parallax barrier type comprises a back panel 11 that provides a plurality of discrete light sources. As shown, the back panel 11 may be formed by way of an areal light source 12 (such as a photoluminescent panel) covered with an opaque mask or barrier layer 13 having a plurality of slits 14a to 14d distributed across its surface. Each of the slits 14 then acts as a line source of light.

25

A liquid crystal display panel (LCD) 15 comprises a plurality of pixels (eg. numbered 1 to 10 in figure 1) which are separately addressable by electrical signals according to known techniques in order to vary their respective light transmission characteristics. The back panel 11 is closely positioned with respect to the LCD panel 15 such that each of the line sources 14 of light corresponds to a group 16 of pixels. For example, pixels 1 to 5

30

shown as group 16<sub>1</sub> correspond to slit 14a, pixels 6 to 10 shown as group 16<sub>2</sub> correspond to slit 14b, etc.

Each pixel of a group 16 of pixels corresponds to one view V of a plurality of possible views ( $V_{-2}$ ,  $V_{-1}$ ,  $V_0$ ,  $V_1$ ,  $V_2$ ) of an image such that the respective line source 14a can be viewed through one of the pixels 1 to 5 corresponding to that view. The number of pixels in each group 16 determines the number of views of an image present, which is five in the arrangement shown. The larger the number of views, the more realistic the 3D effect becomes and the more oblique viewing angles are provided.

Throughout the present specification, we shall refer to the 'image' being displayed as the overall image being generated by all pixels in the display panel, which image is made up of a plurality of 'views' as determined by the particular viewing angle.

A problem exists with this prior art arrangement. The light transmission coefficient of each pixel in the LCD panel is strongly dependent upon the viewing angle. Thus, if all pixels 1 to 5 are driven equally, the viewed intensity of source 14a will appear different for different views. For example,  $V_0$  will be different than  $V_2$ . Thus, the viewed intensity of the source will appear different for different viewing angles.

Conventionally, the perceived intensity of the viewed source for any particular element in an image is an important function of properly rendering grey scales in the image. A conventional display device will provide drive signals to each pixel of a display panel so as to vary its transmission coefficient such that a desired grey scale level is achieved for that element of the image. For the 3D display device described above, if each pixel 1 – 5 is driven at the same voltage, corresponding to the required grey scale for that element of the image, the resulting grey scale image will be a function of viewing angle. This results in a sub-optimal image and unwanted grey scale artefacts when observing the different views of the image.

It is an object of the present invention to overcome or mitigate the unwanted grey scale artefacts in a display device for displaying three

dimensional images in which different views of the image are displayed according to the viewing angle.

According to one aspect, the present invention provides a display device for displaying a three dimensional image such that different views are displayed according to the viewing angle, the display device including:

a display panel having a plurality of separately addressable pixels for displaying said image, the pixels being grouped such that different pixels in a group correspond to different views of the image;

a display driver for controlling an optical characteristic of each pixel to generate a grey scale image according to received image data; and

a grey scale compensation device for further controlling said optical characteristic of at least some pixels within a group to compensate for a predetermined viewing angle dependency of said optical characteristic.

According to another aspect, the present invention provides a method for displaying a three dimensional image on a display device such that different views of the image are displayed according to the viewing angle, the method comprising the steps of:

processing image data to form grey scale pixel data values for each one of a plurality of separately addressable pixels in display panel, the pixels being grouped such that different pixels in a group correspond to different views of the image, the pixel data values each for controlling an optical characteristic of a respective pixel to generate a grey scale image;

applying grey scale correction values to at least some pixel data values within each group to compensate for a predetermined viewing angle dependency of the optical characteristic; and

using the corrected pixel data values to drive pixels of a display panel to generate said image.

Embodiments of the present invention will now be described by way of example and with reference to the accompanying drawings in which:

Figure 1 shows a schematic cross-sectional view of an existing design of LCD device that uses the parallax barrier approach to display three dimensional images;

Figure 1.2 shows a schematic cross-sectional diagram useful in illustrating the geometry of a parallax barrier LCD device;

Figure 3 shows a transmission versus voltage curve for a 90 degree twisted nematic LCD for viewing angles of  $\phi = 0$  degrees (ie. normal to the plane of the display) and for  $\phi = 50$  degrees;

Figure 4 shows a schematic block diagram of a display device according to embodiments of the present invention;

Figure 5 shows an embodiment of the invention utilising a lenticular array;

Figure 6 shows an alternative form of light source suitable for use with the display device; and

Figure 7 shows a graph of viewing angle properties of a conventional liquid crystal display panel useful in illustrating display optimisation principles in accordance with the present invention.

With reference to figure 1, the basic function of a parallax barrier type, three dimensional image display device has already been described. A similar structure of display panel 15 and back panel 11 illumination source may be used in the preferred embodiment of the invention. However, it will be recognised that other configurations may be used as will become evident hereinafter.

In general, the invention uses a display panel 15 having a plurality of separately addressable pixels 1...10, in which the pixels are grouped so that the different pixels 1...5 or 6...10 respectively in a group 16<sub>1</sub> and 16<sub>2</sub> correspond to different views of the image. The display panel 15 may be any suitable electro-optical device in which an optical characteristic of each pixel can be varied according to an electrical control signal to generate an image. Preferably the display panel is a liquid crystal display.

An illumination source having a plurality of discrete light sources 14a ... 14d, so that each group 16 of pixels is positioned to receive light from a respective one of the light sources, is preferably provided. This may be by way of the areal light source 12 and mask 13 arrangement of figure 1, but could also be provided by way of a pixellated light source providing light sources 14 as lines of pixels, individual pixels or blocks of pixels.

Still further, the plurality of discrete light sources could be virtual light sources provided by way of a backlight and lens array (e.g. a lenticular sheet array) providing a series of high intensity light spots. Such an arrangement is illustrated in figure 6. A display device 80 includes an LCD panel 75, areal light source 72 and a lens array 71. The lens array focuses light from the areal source 72 into a plurality of discrete focal points 73 just outside the plane of the LCD panel so that each illuminates a plurality of pixels in the LCD panel, similar to that described in connection with figure 1.

Part of a group of pixels in the display panel 15 is shown in figure 2. A light source 14 of width  $w$  corresponds with, and can be viewed through, a group of pixels 0...7 at respective viewing angles  $\phi_0, \phi_1, \dots \phi_7$  relative to the normal of the plane of the display panel. It will be understood that only half of the pixel group 16 is shown, a further seven pixels being present to the left of pixel 0 to complete the pixel group 16.

Each pixel has a width  $p_0, p_1, \dots p_7$ . Preferably, widths  $p_0 \dots p_7$  are equal, but they could vary in order to compensate to a certain extent for the angle of incidence of light passing therethrough. The distance between the back panel illumination source 14 and the display panel 15 is shown as  $h$ . In a preferred display device,  $h = 2.3$  mm,  $p_0 = 200$  microns, and  $w = 50$  microns although these values may be varied significantly.

Figure 3 shows transmission ( $T$ ) versus voltage ( $V$ ) characteristics for a display panel 15 in the form of a 90 degree twisted nematic LCD. The first curve 31 (solid line) is the  $T$ - $V$  characteristic for a viewing angle  $\phi = 0$  degrees (e.g. pixel 0). The second curve 32 (broken line) is the  $T$ - $V$  characteristic for a viewing angle  $\phi = 50$  degrees (e.g. pixel 5). It will be noted that the variation in transmission coefficient for a pixel viewed at  $\phi = 0$  is such



that to obtain a suitable grey scale range an operating voltage of between 0 and V1 is suggested, depending on the grey scale value required to be displayed. However, it will be noted that use of the same voltage range to drive pixel 5 will result not only in a different set of grey scale values for a given drive voltage, but even a grey scale inversion in that the slope of the T-V characteristic is reversed.

In accordance with the invention, it is thus proposed to use a different range of driving voltages for pixel 5 ( $\phi = 50$  degrees), namely that portion lying between V1 and V2, so that the T-V characteristic for pixel 5 is more closely matched to that of pixel 0.

More generally, an appropriate portion of the T-V characteristic may be selected for each viewing angle  $\phi_0$  to  $\phi_7$  (or for as many angles as are present in the display panel).

Yet more generally, compensation may be made for the variations in slope of the different T-V characteristics of each viewing angle.

Where the T-V characteristics of two different viewing angles are sufficiently close, a common voltage range and/or compensation may be made for those two viewing angles.

The present invention therefore provides a grey scale compensation device that controls the optical characteristic of each pixel 0...7 in a group 16 so as to compensate for the viewing angle.

The grey scale compensation device preferably substantially normalises a grey scale displayed by a group 16 of pixels to that of the other pixels in the group for any given location in the display panel. The perceived grey scale rendering thereby becomes independent of the viewing angle.

Different grey scale correction factors will be required for different display types and for transmissive versus reflective displays. Appropriate grey scale correction factors can be determined from appropriately generated transmission / reflection coefficients determined according to techniques known to the person skilled in the art.

Figure 4 shows schematically exemplary embodiments of a display device 101 incorporating a grey scale compensation device.

An image processor 50 receives a stream of image information including grey scale pixel data for each of a plurality of views  $\phi_0 \dots \phi_7$ . The image information is processed and stored into a frame buffer 51 in digital form so that it can be rendered onto a display device 53. Frame buffer 51 includes a plurality of pages 58, each page including the pixel data for a respective view,  $\phi_0, \phi_1, \dots \phi_7$ .

The frame buffer 51 is accessed by a display driver 52 that provides appropriate drive voltage and/or current signals to each pixel of a display panel 53 in accordance with each of the stored values in frame store 51. As a general principle, it will be understood that the application of grey scale correction values by a grey scale compensation device can be applied either:

(i) by digitally modifying the image data stored in the frame store 51 to include a correction factor so that the value of drive parameter selected by the display driver 52 is suitably modified, or

(ii) by leaving the image data stored in the frame store 51 unmodified, but applying a correction factor to the output of the display driver 52.

In a first embodiment, a grey scale compensation device 60 (shown in dashed outline) is provided as, for example a look-up table accessible by the image processor 50. The look-up table comprises a plurality of pages 61, 62, 63 of correction values, each page corresponding to one of the viewing angles  $\phi_1 \dots \phi_7$  to be applied to image data received by the image processor. The image processor 50 obtains appropriate corrections to the image data and stores this compensated data in frame store 51.

The expression 'correction values' in this context may include 'substitution' values or 'offset' values. In other words, for a given input pixel value  $x_i$ , the look-up tables 61 – 63 may provide a substitution value  $x_s$  (as a function of  $\phi$ ) to be stored in the frame store in place of  $x_i$ . Alternatively, for a given input pixel value  $x_i$ , the look-up tables 61 – 63 may provide an offset value  $x_o$  (as a function of  $\phi$ ) which is combined with the input value and the result  $x_i + x_o$  stored in the frame store in place of  $x_i$ .

A particular advantage of this embodiment is that it can be implemented with very little, if any, change in hardware from a conventional LCD driver arrangement. The functions of the image processor 50 can be realised in software, and the functions of the grey scale compensation device 60 can also  
5 be realised as a software implementation.

In a variation on this first embodiment, the compensation device 60 may operate independently of the image processor 50 upon data already stored in the frame store 51 by the image processor 50. This can be effected by using a second access port 64 to the frame store 51. The compensation device 60 in  
10 this embodiment may also be implemented as a software module, without interfering with the operation of the image processor 50 (for example, where this is a customised graphics processor). Again, the look-up tables 61 – 63 may provide a substitution value or an offset value to be implemented by the grey scale compensation device.

In a second embodiment, it is recognised that the grey scale compensation for each pixel drive signal could be carried out in real time in the analogue domain, i.e. by applying a correction voltage offset to each pixel signal produced by the display driver 52. Thus, in this embodiment, a grey scale compensation device 70 is installed between the display driver 52 and  
20 the display panel 53 to apply specific offset voltages and/or currents to those output by the display driver. In this arrangement, the grey scale correction values may be considered as voltage and/or current offset values.

For the sake of completeness, it is also noted that a hybrid system could deploy both techniques of digital correction values applied to the frame  
25 store 51 by compensation device 60 and analogue offsets applied to the display driver outputs by compensation device 70. An appropriate contribution would be made by both, although this may be a more complicated solution. For example, analogue offsets or correction values applied by the grey scale compensation device 70 might be selected to move the operation of the  
30 display panel into an appropriate portion of the transmission-voltage characteristic 30, while digital correction values might be selected to

compensate for differences in the slope of the transmission-voltage characteristics.

It is also noted that the grey scale compensation device 60 as described herein may also be applied in other forms of 3D display other than that shown in figures 1 and 2. With reference to figure 5, it will be noted that the invention can also be applied to a lenticular 3D display device 200. In this lenticular display device, a liquid crystal display panel 115 includes a plurality of pixels ( $a_1$  to  $b_8$  are shown) arranged in groups 116<sub>1</sub>, 116<sub>2</sub>, in similar manner to that in figure 1. On top of the LCD array 115 is positioned a lenticular array 120 of cylindrical lenses 121, 122. The lenticular array may include any sheet of corrugated optical material, or array of discrete or joined lenses to provide localised focusing for groups of pixels of the LCD panel.

In the arrangement shown in figure 5, the width of each lens element is chosen to be eight pixels, corresponding to an eight-view 3D display. Of course, the width of each lens element may be chosen to correspond to different numbers of pixels according to the angular resolution required. The pixels  $a_1$  to  $a_8$  of the LCD are imaged into the different views. For example, the light rays emitted from pixels  $a_2$  and  $a_4$  are shown. One sees that in the LCD substrate 116, the rays emitted by pixel  $a_2$  propagate to a large extent obliquely with respect to the rays emitted by pixel  $a_4$ . The angle between them is, on average, approximately equal to the angle between the two views ( $\theta$ ).

It will be seen that in a lenticular-type 3D display device, the light rays of the different views travel through the liquid crystal layer at different angles. Therefore, the problem of grey scale dependency of the angle still exists, and is solved by the grey scale compensation device 70 as described in connection with figure 4.

The invention as described above also has important implications for the optimisation of liquid crystal displays generally. The viewing angle dependence of LCD panels is known generally to be rather poor. Figure 7 illustrates how contrast and grey scale inversion depends upon viewing angle for a standard 90 degree twisted nematic (TN) transmissive LCD without compensation foil. The horizontal viewing angle is shown on the x-axis

between  $-60$  degrees and  $+60$  degrees from the normal to the plane of the display, and the vertical viewing angle is shown on the y-axis between  $-60$  degrees and  $+60$  degrees from the normal to the plane of the display.

The orientations of the optical axes 90, 91 of the LCD polarisers and the optical axes 92 of the liquid crystal directors are shown in the lower part of the figure.

From figure 7, it is seen that the image quality strongly depends upon viewing angle. For the example shown in figure 7, the optimal viewing angles are represented by the diagonal line 94 running from top left to bottom right, and grey scale inversion occurs for viewing positions to the right and above the line 94.

Conventionally, for most important applications such as televisions and computer monitors, it is recognised that maximising performance for horizontal viewing directions is more important than maximising performance for vertical viewing directions. For example, for television applications, multiple viewers of a display device will normally be arranged with their eye levels more-or-less consistent relative to the screen (i.e. with very little variation along the y-axis), but their horizontal viewing angles relative to the x-axis may vary significantly. Similarly, a user seated at a computer monitor is more likely to vary head position along the x-axis while working, than along the y-axis.

According to convention, therefore, the LCD would be rotated anticlockwise through  $45$  degrees from the orientation shown in figure 7, such that its polarisation axes are at approximately  $45$  degrees to the x- and y-axes of the display when in use. In this way, the performance of the display device is optimised for horizontal viewing angles, but is compromised for vertical viewing angles.

3D LCD displays suffer from the same problems with optimisation of viewing angle dependency in respect of x and y directions.

However, in the present invention, it is recognised that optimisation of grey scale rendering can be achieved by electronic techniques in driving the

display, using the described grey scale compensation device 60 and/or 70 as described above.

Therefore, it is more appropriate to provide the display device with an orientation in which the inherent optical characteristics of the display panel are optimised for vertical viewing angle variations. Horizontal viewing angle variations are accommodated for and optimised using the electronic driving techniques as described herein.

Thus, in a preferred arrangement, the 3D display device described above is arranged so that, in normal use, it has the pixels within each group 16 that provide different views as a function of angle to a first axis of the display panel, and has the polarising elements of the display panel oriented so as to minimise viewing angle dependence relative to a second axis of the display, where the second axis is orthogonal to the first axis.

In a most general sense, the inherent optical characteristics of the display panel are such that viewing angle dependence is reduced or substantially minimised relative to the y-axis and the grey scale compensation device 60 and/or 70 serves to reduce or substantially minimise viewing angle dependence relative to an axis that is transverse to the y-axis. More preferably, the grey scale compensation device 60 and/or 70 serves to reduce or substantially minimise viewing angle dependence relative to an axis that is orthogonal to the y-axis (i.e. the x-axis). In a most preferred device, the x-axis is defined as the horizontal axis when the display is in normal use, and the y-axis is defined as the vertical axis when the display is in normal use.

Other embodiments are intentionally within the scope of the accompanying claims.

## CLAIMS

1. A display device (101) for displaying a three dimensional image such that different views are displayed according to the viewing angle, the display device including:

5 a display panel (15, 53) having a plurality of separately addressable pixels (0...10) for displaying said image, the pixels being grouped such that different pixels in a group (16) correspond to different views of the image;

a display driver (52) for controlling an optical characteristic of each pixel to generate a grey scale image according to received image data; and

10 a grey scale compensation device (60, 70) for further controlling said optical characteristic of at least some pixels within a group to compensate for a predetermined viewing angle dependency of said optical characteristic.

2. The display device of claim 1 further including a back panel (11) for  
15 providing a plurality of discrete sources (14) of illumination, each group (16) of pixels in the display panel (15) being positioned to receive light from a respective one of the discrete sources of illumination.

3. The display device of claim 2 in which the back panel (11) provides a  
20 plurality of line sources of illumination.

4. The display device of claim 2 in which the back panel (11) provides a plurality of point sources of illumination.

25 5. The display device of claim 2 in which the display panel (15) is a light-transmissive display panel adapted for viewing from a side opposite to the side on which the back panel (11) is located.

6. The display device of claim 1 further including a lenticular array (120)  
30 positioned adjacent to the display panel (15), each lenticle (121, 122) within the array focusing light from selected pixels in the display panel.

7. The display device of claim 6 in which each lenticle (121, 122) within the array (120) is associated with a said group (16) of pixels.

5 8. The display device of any preceding claim in which the optical characteristic is a light transmission characteristic and the display driver (52) and grey scale compensation device (60, 70) are adapted to control the amount of light passing through each pixel according to a grey scale image to be displayed.

10 9. The display device of any preceding claim in which the grey scale compensation device (60) comprises a look-up table containing correction values to be applied in respect of each pixel within a group.

15 10. The display device of claim 8 in which the correction values are selected according to the viewing angle of a respective pixel within the group (16).

20 11. The display device of claim 10 in which the correction values are selected so as to substantially normalise a grey scale intensity displayed by a group of pixels to be independent of the viewing angle.

25 12. The display device of claim 9 in which the look-up table includes substitution values or offset values as a function of viewing angle to be applied to a frame store.

30 13. The display device of claim 8 in which the grey scale compensation device comprises a transmission versus voltage characteristic, the grey scale compensation device adapted to adjust a pixel drive voltage and/or current received from the display driver.



14. The display device of claim 13 in which the grey scale compensation device provides a voltage and/or current offset to the pixel drive voltage and/or current received from the display driver.

5 15. The display device of any preceding claim in which the inherent optical characteristics of the display panel (15, 53) are configured such that viewing angle dependence is reduced or substantially minimised relative to the y-axis and the grey scale compensation device (60, 70) serves to reduce or substantially minimise viewing angle dependence relative to an axis that is  
10 transverse to the y-axis.

16. The display device of claim 15 in which the grey scale compensation device (60, 70) serves to reduce or substantially minimise viewing angle dependence relative to an axis that is orthogonal to the y-axis (i.e. the x-axis).

15

17. The display device of claim 16 incorporated into an object, in which the x-axis is defined as the horizontal axis when the object is in normal use, and the y-axis is defined as the vertical axis when the object is in normal use.

20 18. A method for displaying a three dimensional image on a display device such that different views of the image are displayed according to the viewing angle, the method comprising the steps of:

processing image data to form grey scale pixel data values for each one of a plurality of separately addressable pixels (0...10) in display panel (15, 53),  
25 the pixels being grouped such that different pixels in a group (16) correspond to different views of the image, the pixel data values each for controlling an optical characteristic of a respective pixel to generate a grey scale image;

applying grey scale correction values to at least some pixel data values within each group to compensate for a predetermined viewing angle  
30 dependency of the optical characteristic; and

using the corrected pixel data values to drive pixels of a display panel to generate said image.

19. The method of claim 18 in which the optical characteristic is a light transmission characteristic and the grey scale correction values applied are adapted to control the amount of light passing through each pixel according to a three dimensional grey scale image to be displayed.

20. The method of claim 18 in which the grey scale correction values are obtained from a look-up table containing correction values to be applied in respect of each pixel within a group.

21. The method of claim 19 in which the correction values are selected according to the viewing angle of a respective pixel within the group (16).

22. The method of claim 21 in which the correction values are selected so as to substantially normalise a grey scale displayed by a group of pixels to be independent of the viewing angle.

23. The method of claim 19 in which the grey scale correction values are derived from a transmission versus voltage characteristic of the display panel, the corrected pixel data values being used to adjust a pixel drive voltage and/or current applied to the display panel.

24. The method of any one of claims 18 to 23 further including the step of configuring the inherent optical characteristics of the display panel (15, 53) such that viewing angle dependence is reduced or substantially minimised relative to the y-axis and applying said grey scale correction values so as to reduce or substantially minimise viewing angle dependence relative to an axis that is transverse to the y-axis.

25. The method of claim 24 in which the grey scale correction values are applied to reduce or substantially minimise viewing angle dependence relative to an axis that is orthogonal to the y-axis (i.e. the x-axis).

26. The method of claim 25 in which the x-axis is the horizontal axis when the display panel is in normal use, and the y-axis is the vertical axis when the display panel is in normal use.

5

27. A computer program product, comprising a computer readable medium having thereon computer program code means adapted, when said program is loaded onto a computer, to make the computer execute the procedure of any one of claims 18 to 26.

10

28. A computer program, distributable by electronic data transmission, comprising computer program code means adapted, when said program is loaded onto a computer, to make the computer execute the procedure of any one of claims 18 to 26.

15

29. Apparatus substantially as described herein with reference to the accompanying drawings.



30. A method substantially as described herein with reference to the accompanying drawings.

20

**ABSTRACT****IMPROVING GREY SCALE CONTRAST IN A 3D IMAGE DISPLAY DEVICE**

A display device for displaying a three dimensional image such that different views are displayed according to the viewing angle has a display panel with a plurality of separately addressable pixels for displaying said  
5 image. The pixels are grouped such that different pixels in a group correspond to different views of the image. A display driver controls a transmission characteristic of each pixel to generate an image according to received image data. The drive signals applied to each pixel in the display panel are adjusted  
10 using grey scale correction values that vary the optical transmission of each pixel within a group so as to produce an image grey scale for each point in the image that is independent of viewing direction.

[Figure 4]







Fig. 3

Fig 4






Fig. 5






Fig. 6




Fig. 7

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**